

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 October 2005 (20.10.2005)

PCT

(10) International Publication Number
WO 2005/099001 A1

(51) International Patent Classification⁷: **H01M 4/86**, 4/88

(74) Agent: **GOTO, Masaki**; Shoyu-Kaikan, 3-1, Kasumigaseki 3-chome, Chiyoda-ku, Tokyo 1000013 (JP).

(21) International Application Number:

PCT/JP2005/002952

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 17 February 2005 (17.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2004-101373

30 March 2004 (30.03.2004) JP

(71) Applicant (*for all designated States except US*): **NISSAN MOTOR CO., LTD.** [JP/JP]; 2, Takara-cho, Kanagawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): **OHMA, Atsushi** [JP/JP]; 43-20, Ohoka 1-chome, Minami-ku, Yokohama-shi, Kanagawa 2320061 (JP). **ONO, Yoshitaka** [JP/JP]; 15-8-505, Morisaki 3-chome, Yokosuka-shi, Kanagawa 2380023 (JP). **SHIMOI, Ryoichi** [JP/JP]; 36-13, Tomiokanishi 4-chome, Kanazawa-ku, Yokohama-shi, Kanagawa 2360052 (JP). **TAJIRI, Kazuya** [JP/US]; 329 Toftrees Ave., Apt. #227, State College, Pennsylvania 16803 (US).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUEL CELL



(57) Abstract: A fuel cell (1) comprises a cathode catalyst layer (3) and an anode catalyst layer (4) disposed on each surface of an electrolyte membrane (2), an oxidant gas passage (8) facing the cathode catalyst layer (3), and a fuel gas passage (9) facing the anode catalyst layer (9). The cathode catalyst layer (3) contains a metal catalyst (16). In a region (A), in which the differential electric potential between the cathode catalyst layer (3) and the electrolyte membrane (2) is larger than in another region, the metal catalyst (16) content of the cathode catalyst layer or the specific surface area of the metal catalyst (16) in the form of minute parti

WO 2005/099001 A1